


HDC-50LX Series Hall Current Sensor

Introduction

HDC-50LX Series Hall current transducer is the new generation product based on Hall effect. It is able to measure DC, AC, pulse and other currents with irregular waves under the condition of electrical isolation.

△Electrical Parameters (Ta=25°C)

Type		HDC-05LX	HDC-10LX	HDC-20LX	HDC-30LX	HDC-50LX
Parameters	Symbols					
Nominal measuring current	I_{PN}	$\pm 5A$	$\pm 10A$	$\pm 20A$	$\pm 30A$	$\pm 50A$
Linear range	I_p	$0\sim\pm 10A$	$0\sim\pm 20A$	$0\sim\pm 40A$	$0\sim\pm 60A$	$0\sim\pm 100A$
Nominal output voltage	V_{SN}	$\pm 4V\pm 0.04V(R_L=10K\ \Omega)$				
Zero offset voltage	V_O	$\leq\pm 0.04V(I_{PN}=0)$				
Temperature drift of bridge offset	V_{OT}	$\leq\pm 1.5mV/^\circ C$				
Linear error	ξ_L	$\pm 1\%$				
Response time	T_r	$\leq 3\ \mu S$				
Supply voltage	V_C	$\pm 15V\pm 5\%$				
Isolation voltage	V_d	2.0KV/50 or 60HZ/1min				
Power dissipation current	I_C	$\pm 20mA$				
Frequency bandwidth	f	DC~50KHZ(-3dB)				
Operating temperature	T_a	$-25^\circ C\sim+85^\circ C$				
Storage temperature	T_s	$-40^\circ C\sim+90^\circ C$				



Features:

- ◆ Use open-loop current transducer based on Hall effect
- ◆ Adopt UL94V-0-recognized insulated casing
- ◆ Small size and space saving
- ◆ Low power consumption
- ◆ High immunity against external disturbance

Applications:

- ◆ AC variable-frequency speed control system and servo motor
- ◆ Uninterruptible power supplies (UPS)
- ◆ Switched-mode power supply
- ◆ Power supply for electric welding machine

Instructions for Use:

- ◆ Connect the wire of transducer in correct way as required.
- ◆ Inputting measured current from input end of transducer, the in-phase voltage signal can be obtained from output end by sampling.

△Dimension :(mm)

